

Delaware Department of Transportation

**QUESTIONS AND ANSWERS**

**T201347204.01**

**Provide Precast Elements for BR3-463 on S396 West Line Rd**

**Monday, January 28, 2013**

<b>Q #</b>	<b>Question</b>	<b>Answer</b>
9	Can you please extend the bid date because we would like to put a responsible number on this project.	We are unable to extend at this time.
8	Do the keyways need to be grouted?	See the spec for 602738.
7	Are keyways required at the joints and what size do they need to be?	See notes 7B & C. Size shall be for the precaster to propose methods that allow for easiest construction.
6	And if a gasket is required is the gasket to be full size or full depth of the precast element?	For the precaster to propose so long as the results satisfy Notes 4 and 7A.
5	Is a gasket required between all joints of the precast items?	See Plan Note 7A
4	What is the size and the depth of the post tensioning pockets?	For the precaster to propose methods that allow for easiest construction.
3	Is the strand sheathed or unsheathed?	See the spec, ('sheathed').
2	Is there a specific strand size that is required?	See the spec for item 602739.
1	Review of the bid documents, sheets 1 thru 3, shows that an omission has been made on sheet 3. In the upper left corner of the sheet, the detail marked "Precast Rigid Frame Section" shows a bar callout near the left side of the detail as "# BAR @ 9" (TYP.)" There is no bar size called out after the # symbol. Please provide the desired bar size so we may complete our material takeoffs.	Addressed in Clarification posted on website.